

ROCKSILK® FLEXIBLE SLAB

June 2021



APPLICATIONS



DESCRIPTION

Rocksilk® Flexible Slab is a Rock Mineral Wool slab, designed for use in multiple thermal and acoustic applications as well as the fire protection of a loft conversion floor. It is non-combustible with the best possible Euroclass A1 reaction to fire classification, and is manufactured using Knauf Insulation's unique bio-based binder, ECOSE® Technology.

PERFORMANCE

Thermal

Thermal conductivity: 0.035 and 0.037 W/mK

Fire

Classification: Euroclass A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00 MNs/g.m

BENEFITS

- ✓ Multi-purpose product which can be used to insulate a wide range of applications on site.
- ✓ Flexible on all four sides for quick and simple installation.
- ✓ Existing ceilings can be retained on a loft upgrade whilst meeting building regulations.

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Pieces per pack	Area per pack (m ²)	Packs per pallet	Product code
140	0.035	4.00	1200	600	3	2.16	12	2411335
100	0.037	2.70	1200	600	6	4.32	12	457994
90	0.037	2.40	1200	600	6	4.32	12	457997
70	0.037	1.85	1200	600	8	5.76	12	2411408
60	0.037	1.60	1200	600	10	7.20	12	457996
50	0.037	1.35	1200	600	12	8.64	12	457995
40	0.037	1.05	1200	600	14	10.08	12	531594

All dimensions are nominal

CERTIFICATIONS, CLASSIFICATIONS AND INDUSTRY STANDARDS



ROCKSILK® FLEXIBLE SLAB

June 2021

ADDITIONAL INFORMATION

Durability

Rocksilk® Flexible Slab is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria. The product will have a life equivalent to that of the structure in which it is incorporated.

Application

Rocksilk® Flexible Slab is typically used for the thermal and acoustic insulation of a wide variety of constructions such as timber and metal stud partitions, timber frame walls and suspended timber floors. Rocksilk® Flexible Slab has been tested to provide 60 minutes fire protection when a loft is upgraded into habitable accommodation.

Standards and Certification

Rocksilk® Flexible Slab is manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by TÜV Nord.

Real performance

Glass and Rock Mineral Wool are easier to install correctly than other insulants such as rigid boards because they adapt to any slight imperfections in the substrate and knit together, eliminating any air gaps. Evidence shows the absence of air gaps is crucial to achieving real performance in the relevant application.

Environmental

Rocksilk® Flexible Slab contains no ozone-depleting substances or greenhouse gases. For further environmental information consult the relevant Environmental Product Declaration, available on our website.

Handling and storage

Rocksilk® Flexible Slab is easy to handle and install, being lightweight and easily cut to size, where necessary. Rocksilk® RainScreen Slab is supplied in recyclable polythene packs (4-LDPE) which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Rocksilk® Flexible Slab should not be left permanently exposed to the elements.



ECOSE® Technology is our unique bio-based binder, that is used in the manufacture of all of our Glass Mineral Wool products and the majority of our Rock Mineral Wool products, to bind insulation strands together. ECOSE® Technology contains no added formaldehyde or phenol. It is made from natural raw materials that are rapidly renewable and is 70% less energy-intensive to manufacture than traditional binders, so it is more environmentally friendly. Products made with ECOSE® Technology are soft to touch and easy to handle. They generate low levels of dust and VOCs and have been awarded the Eurofins Gold Certificate for Indoor Air Comfort.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St. Helens, Merseyside, WA10 3NS. UK

Customer Service: 01744 766 766 Technical Support Team: 01744 766 666

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatsoever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1518DAT-V0621

challenge.
create.
care.